

Standard-Level Analytical Balances

# HR-AZ/HR-A

Series



HR-250AZ



HR-250A



*Pay for What Matters—Reliable,  
Accurate Weighing*

**AND**  
A&D Company, Ltd.

Discover Precision

[www.aandd.jp](http://www.aandd.jp)

# Finally, Globally Proven Precision at a Fair Price

What do you expect most from an analytical balance? If you are like us, you will agree that accuracy and reliability come before anything else. The HR-AZ/HR-A series, behind their simple design, utilize proven A&D sensor technology that delivers solid performance to all users who wish to do superior work.

Optimizing value, the HR-AZ/HR-A series realizes the following three savings:

## 1. Saving “Time”

### Fast stabilization in 2 seconds

Our widely-recognized Compact Super Hybrid Sensor (C-SHS) technology ♦ now enables you to perform high-speed, frustration-free weighing even at a readability of 0.1 mg. ♦ Patented

### One-touch automatic calibration (HR-AZ models only)

The built-in calibration mass lets you ensure the accuracy of your balance with just one key press.

## 2. Saving “Space”

### Compact footprint: 198 mm × 294 mm

With the C-SHS, the footprint of the balance is smaller than the ISO A4 (210 mm × 297 mm) paper size, maximizing opportunities for use of an analytical balance in even the smallest of spaces.

### Rotary sliding doors

Unlike conventional analytical balances, the HR-AZ/HR-A series requires no extra space at the rear for accessing the weighing chamber, as the doors simply rotate behind the balance.

### Removable breeze break

The breeze break is easily removed using a unique clip system, allowing fast, simple cleaning and use in confined spaces like gloveboxes and controlled environment cabinets.

Rotary sliding doors



## 3. Saving “Cost”

### Lean design for affordability

The HR-AZ/HR-A design is all about “keeping it simple” without compromising quality or performance. Key features demanded by today’s market have been included, resulting in a compact, precise, and reliable analytical balance for the value-conscious user.

## Superb Usability

### Large removable breeze break with antistatic coating

The breeze break is treated with an antistatic agent to ensure stable weighing. It also offers a large working space and can be detached for better portability and easy cleaning of the balance.



Removable breeze break

### Clear, reverse backlit LCD

The contrast of the black and white display provides excellent visibility even in a dimly-lit area.

### Front-mounted spirit level

The spirit level is easy to see when adjusting the leveling feet of the balance for accurate weighing.

## Great Flexibility and Compliance

### GLP/GMP/GCP/ISO compliant output

For compliance and documentation requirements, the HR-AZ/HR-A series can output the balance manufacturer, model, serial number, ID number, date and time\*<sup>1</sup>, space for signature, and calibration records.

\*<sup>1</sup> For the HR-AZ models only. Please use the AD-8127 compact printer, which has a calendar function, to print the date and time with the HR-A models.

### User access control (UAC) with password function

The balance can be password-protected to allow only authorized individuals to use it or change its settings. It is also possible to disable any change to the balance settings including calibration or, for HR-AZ models, correction of the internal mass value.

### Adjustable response characteristics and hold function

From three preset combinations of weighing speed and stability (FAST, MID, or SLOW), select the one that best suits your environmental conditions (drafts and vibrations). A hold function is also available for weighing animals.

### Statistical calculation function

The balance displays and outputs statistical calculation data including number of data, sum, maximum, minimum, range (maximum–minimum), average, standard deviation, and coefficient of variation.

## Options and Accessories

### Quick USB interface (FXi-02)

The easy-to-use USB interface requires no driver or software installation for transfer of weighing data to a PC\*<sup>2</sup>.

\*<sup>2</sup> Data transfer from the balance to a PC only. Please use the RS-232C standard interface with the serial-USB converter (AX-USB-9P, optional) for two-way communication or sending GLP or statistical calculation information via USB. Portable memory devices such as weighing environment logger (AD-1687) and data logger (AD-1688) are also available.

### Ethernet interface with WinCT-Plus software (FXi-08)

You can send commands for controlling and acquiring data from multiple balances.



### Rechargeable battery unit (FXi-09)

The Ni-MH rechargeable battery pack can be fitted into the balance for use without AC power (10 hours of charging for 14 hours of operation).

### Density determination kit (AD-1654)

Using this kit, it is easy to calculate the density of a solid or liquid substance in density mode.

# Specifications

Models	HR-250AZ	HR-251AZ	HR-150AZ	HR-100AZ	HR-250A	HR-251A	HR-150A	HR-100A
Capacity	252 g	62 g / 252 g*	152 g	102 g	252 g	62 g / 252 g*	152 g	102 g
Readability	0.1 mg	0.1 mg / 1 mg	0.1 mg			0.1 mg / 1 mg	0.1 mg	
Repeatability (standard deviation)	0 to 200 g: 0.1 mg 200 to 252 g: 0.2 mg	0.1 mg / 0.5 mg	0.1 mg			0 to 200 g: 0.1 mg 200 to 252 g: 0.2 mg	0.1 mg / 0.5 mg	0.1 mg
Minimum weight*ii (typical)	140 mg							
Linearity	±0.3 mg	±0.3 mg / ±1 mg	±0.2 mg			±0.3 mg	±0.3 mg / ±1 mg	±0.2 mg
Stabilization time (when set to FAST under a good environment)	Approx. 2 seconds*iii							
Sensitivity drift	±2 ppm/°C (10 to 30 °C/50 to 86 °F)							
Internal calibration	Yes				No			
Clock and calendar function	Yes				No			
Operating environment	5 to 40 °C (41 to 104 °F), 85% RH or less (no condensation)							
Display type	Reverse backlit LCD							
Display refresh rate	5 times/second (10 times/second can be selected)							
Units of measure*iv	g (gram), mg (milligram), oz (ounce), ozt (troy ounce), ct (metric carat), mom (momme), dwt (pennyweight), gr (grain), pcs (counting mode), % (percent mode), SG (density mode), and a user-programmable unit							
Counting mode	Minimum unit mass	0.1 mg	1 mg	0.1 mg			1 mg	0.1 mg
	Number of samples	10, 25, 50 or 100 pieces						
Percent mode	Minimum 100% reference mass	10.0 mg	100 mg	10.0 mg			100 mg	10.0 mg
	% readability	0.01%, 0.1%, or 1% (depends on the reference mass stored)						
Interface	RS-232C							
Applicable calibration weight value	250 g, 200 g 100 g, 50 g	250 g, 200 g 100 g, 50 g, 20 g	150 g, 100 g, 50 g	100 g, 50 g	250 g, 200 g 100 g, 50 g	250 g, 200 g 100 g, 50 g, 20 g	150 g, 100 g, 50 g	100 g, 50 g
Weighing pan size	Ø90 mm							
External dimensions	198 (W) × 294 (D) × 315 (H) mm							
Net weight	Approx. 3.9 kg				Approx. 3.5 kg			
Power supply	AC adapter							
Power consumption	Approx. 11 VA (supplied to the AC adapter)							

\*i Smart range function: The readability will switch to 1 mg automatically when the display value exceeds 62 g but returns to 0.1 mg by pressing the RE-ZERO key.  
 \*ii Pursuant to the United States Pharmacopeia (USP), Chapter 41  
 \*iii The factory setting is MID, whose stabilization time is approx. 3 seconds.  
 \*iv One additional unit from tael (Singapore/HK jewelry/Taiwan/China), tola or Newton can be added upon request.

## Options

FXi-02\*<sup>v</sup> Quick USB interface with cable

FXi-08\*<sup>v</sup> Ethernet interface with WinCT-Plus software

FXi-09\*<sup>v</sup> Built-in rechargeable battery

FXi-10 Small breeze break

FXi-11 Large breeze break

\*<sup>v</sup> The FXi-02, FXi-08 and FXi-09 cannot be used at the same time



## Accessories

AD-1654 Density determination kit

AD-1671 Anti-vibration table for balances

AD-1672 Tabletop breeze break

AD-1683 Static eliminator

AD-1684A Electrostatic field meter

AD-1687 Weighing environment logger

AD-1688 Weighing data logger

AD-1689 Tweezers for calibration weight

AD-8127 Compact printer

AD-8526 Serial/Ethernet converter

AD-8527 Quick USB adapter

AD-8920A Remote display

AD-8922A Remote controller

AX-FXi-31 Main unit cover (5 pcs)

AX-USB-9P Serial/USB converter with cable



## Discover Precision

**A&D Company, Ltd.**

3-23-14 Higashi-Ikebukuro, Toshima-Ku, Tokyo, 170-0013, Japan Tel: +81 3-5391-6132 Fax: +81 3-5391-1566 www.aandd.jp

**A&D Engineering, Inc.**

1756 Automation Parkway, San Jose, CA 95131, U.S.A. Tel: +1 408-263-5333 Fax: +1 408-263-0119

**A&D Australasia Pty Ltd.**

32 Dew Street, Thebarton, South Australia 5031, Australia Tel: +61 8-8301-8100 Fax: +61 8-8352-7409

**A&D Instruments Ltd.**

Unit 24/26 Blacklands Way, Abingdon Business Park, Abingdon, Oxfordshire, OX14 1DY, United Kingdom Tel: +44 1235-550420 Fax: +44 1235-550485

**<German Sales Office>**

Hamburger Straße 30, D-22926, Ahrensburg, Germany Tel: +49 4102-459230 Fax: +49 4102-459231

**A&D Korea Ltd.**

8F Manhattan Bldg., 33, Gukjegeumyung-ro 6-gil, Yeongdeungpo-gu, Seoul, 07331, Korea Tel: +82 2-780-4101 Fax: +82 2-782-4280

**A&D Rus Co., Ltd.**

Vereyskaya Str. 17, 121357, Moscow, Russia Tel: +7 495-937-33-44 Fax: +7 495-937-55-66

**A&D Instruments India (P) Ltd.**

509 Udyog Vihar Phase V Gurgaon-122 016, Haryana, India Tel: +91 (124) 471-5555 Fax: +91 (124) 471-5599