Reliable DO documentation...

... with the ProfiLine Oxi 3310

The Oxi 3310 is a combination of a robust portable meter and data logger for gathering measuring data automatically and PC supported evaluation.

ProfiLine Oxi 3310

- Waterproof USB interface for fast data transfer
- Data output in .csv format
- Calibration versus external standard possible (Winkler-titration)



Complete as SET

Measuring safety

- Repeatable measuring results provided by the active, automatic AutoRead function with recognition of stable end values
- Automatic air-pressure compensation
- Silicone keypad with tangible key click, optional protective armor for field operation

GLP/AQA documentation

 Transfer of all data in .csv format via USB interface to PC, on demand formatted transfer into Excel (MultiLab® Importer, included in the delivery scope or as download).

Flexible and powerful:

- Measures partial pressure, concentration and saturation
- Salinity corrections
- Storage for large measuring batches



62


Measuring DO precisely...

... with the ProfiLine Oxi 3210

The ProfiLine Oxi 3210: A top-class portable DO measuring instrument - with modern, user-friendly interface.

ProfiLine Oxi 3210

- Convenient user guidance
- Manual storage function
- For galvanic DO sensors



ProfiLine Oxi 3210

Measuring safety


- Repeatable measuring results provided by the active, automatic AutoRead function with recognition of stable end values
- Automatic air-pressure compensation
- Silicone keypad with tangible key click, optional protective armor for field operation

GLP/AQA documentation

• Storage with data output display or occasional documentation.

Flexible and powerful:

- Measures partial pressure, concentration and saturation
- Salinity corrections
- Storage for large measuring batches



Measuring DO easily...

... with the ProfiLine Oxi 3205

The Oxi 3205 is an easy-to-use, reliable measuring instrument for routine measurements.

ProfiLine Oxi 3205

- Suitable for CellOx® or DurOx® sensors
- Backlit graphic display
- Automatic air-pressure compensation



Measuring safety

- Repeatable measuring results provided by the active, automatic AutoRead function with recognition of stable end values
- Safe operation: Automatic functions reduce the number of keys (6).
- OxiCal® air-calibration
- Waterproof 8-pin socket for measurements in the field.

GLP/AQA documentation

Transfer of all data in .csv format via USB interface to PC, on demand formatted transfer into Excel (MultiLab® Importer, included in the delivery scope or as download).

Flexible and powerful:

- Silicone keypad with tangible key click, can be operated with gloves
- For field operation available in a case set with proven sensors

Model	Oxi 3205	Oxi 3210	Oxi 3310	
2	0.00 20.00 mg/l (20.0 mg/l*) ±0.5 % of value; 0 90 mg/l ±0.5 % of value			
Accuracy O ₂ part. pressure	0.0 200.0 % (200 %*) ±0.5 % of value; 0 600 % ±0.5 % of value 0.0 200.0 mbar (200 mbar*) ±0.5 % of value, 0 1250 mbar ±0.5 % of value -5.0 +105.0 °C ±0,1 °C (23 221 °F)			
Temperature compensation	Better than 2% at 0 +40 °C (32 104 °F)			
Air pressure compensation	Automatic with built-in pressure sensor (500 1100 mbar)			
Salinity correction	0 or 35 fixed	Automatic from 0.0 70.0), adjustable via display	
Calibration	OxiCal® rapid calibration in OxiCal®-SL or OxiCal®-D			
Memory/Logger	-	Manual 200	Manual 500/5000 autom	atic
Display	LCD Graphic, backlit			
Continuous operation	Up to 800 hrs. without/100 hrs. with backlight			
Ordering Infor	mation			
ProfiLine Portable Dissolved Oxyg	gen Meter SETs			Order No.
Oxi 3205 SET 3	Robust and waterproof portable dissolved oxygen meter for battery operation, case set with DurOx® 325 and accessories			2BA103
Oxi 3210 SET 1	Robust and waterproof portable dissolved oxygen meter including memory, for battery operation, case set with CellOx® 325 and accessories			2BA201
Oxi 3310 SET 1	Robust and waterproof portable dissolved oxygen meter including memory, data logger and USB mini 2BA3 B interface, for battery operation, case set with CellOx® 325 and accessories			









* if DurOx® DO sensor is used